



SPH-200H/225H/280H/320H/380H/450H

SERIES HYDRAULIC POWER HACK SAWS



SPH-280H



SPH-380H

STANDARD EQUIPMENT:

- Complete hydraulic system.
- Infinitely variable saw feed pressure control.
- Complete electric components with motor protection.
- Recirculating coolant system.
- Adjustable material length stop.
- Clamping device for short ends.
- Equalizing bar for jaws.
- Material support stands.
- One saw blade ready for cutting.
- One set of necessary tools, and tool box.
- One grease gum.
- One instruction and parts manual.

SPECIFICATIONS:

MODELS	UNIT	SPH-200H	SPH-225H	SPH-280H	SPH-320H	SPH-380H	SPH-450H
Cutting capacity	● mm(in)	200(7 7/8)	225(8 7/8)	280(11)	320(12 5/8)	380(15)	450(17 3/8)
	■ mm HxW (in)	190x190 (7 3/8 x 7 3/8)	225x220 (8 7/8 x 8 13/16)	280x250 (11 x 9 3/8)	300x300 (11 3/4 x 11 3/4)	330x350 (13 x 13 3/4)	380x430 (15 x 17)
Max. Cutting Degree	mm	45°/80	45°/120	45°/140	45°/185	45°/185	45°/250
Distance of Strokes	mm	118	138	138	138	138	155
Strokes per		105, 125			80, 100, 120		
Blade Size	mm	350x32x1.6x8.3	400x32x1.6x8.3	450x32x1.6x8.3	500x38x2x10.3	550x45x2.25x10.3	650x50x2.5x12.3
	(in)	(14x1 1/4 x 1/16 x 1/32)	(16x1 1/4 x 1/16 x 1/32)	(18x1 1/4 x 1/16 x 1/32)	(20x1 1/2 x 1/8 x 1/32)	(22x1 3/4 x 1/2 x 1/32)	(26x2 x 1/8 x 1/2)
Main motor	HP(KW)	4P, 1HP(0.75)	4P, 2HP(1.5)	4P, 2HP(1.5)	4P, 2HP(1.5)	4P, 2HP(1.5)	4P, 3HP(2.2)
Measurement (LxWxH)	mm	1240x730x1010	1420x850x1100	1420x850x1100	1550x850x1200	1550x850x1200	1970x940x1400
	(in)	(48 3/8 x 28 3/8 x 39 3/8)	(55 7/8 x 33 1/8 x 43 3/8)	(55 7/8 x 33 1/8 x 43 3/8)	(61 x 33 1/4 x 47 3/8)	(61 x 33 1/4 x 47 3/8)	(77 3/8 x 37 x 55)
Weight	kgs	270/330	415/475	430/490	450/520	475/ 545	715/810
Net/Gross	(lbs)	(594/726)	(915/1047)	(948/1080)	(992/1146)	(1047/1201)	(1576/1786)

● All specifications and designs are subject to change without notice.

f FREJO TH INTERNATIONAL LTD.

8F #501, SEC.2, WU CHUAN W. RD., TAICHUNG 408, TAIWAN, R.O.C.

TEL:886-4-23816977

FAX:886-4-23813584.23813769

E-mail: mail@frejoth.com.tw

web-site <http://www.frejoth.com.tw>